

# Laserliner

## ThermoSensor Clamp



K-type temperature sensor with  
heat resistant handle

Rev18W50



- K-type temperature sensor for metallic pipes with diameters ranging from 6 to 35 mm
- High clamping force for a secure grip.
- Long measuring cable suitable for complex installations
- Heat resistant handle

For ThermoMaster,  
ThermoSpot XP,  
CondenseSpot XP,  
MultiMeter XP and  
ClampMeter XP



### TECHNICAL DATA

**MEASUREMENT RANGE** -40°C ... 100°C

**ACCURACY**  $\pm 2,5^{\circ}\text{C}$

**PIPE DIAMETER**  
6 mm ... 35 mm

**OPERATING CONDITIONS**  
-10°C ... 60°C, Max. humidity 80% rH,  
no condensation, Max. working altitude  
4000 m above sea level

**STORAGE CONDITIONS**  
-20°C ... 70°C,  
Max. humidity 80% rH

**CABLE LENGTH** 1,5 m

**DIMENSIONS** (W x H x D)  
130 x 79 x 39 mm (without cable)

**WEIGHT**  
100 g



### ThermoSensor Clamp

**Packing dimension** (W x H x D)  
90 mm x 200 mm x 55 mm



ARTICLE	ARTICLE NO	EAN-CODE	PU
ThermoSensor Clamp	082.438A	4 021563 706235	2

